

TimeTools TA210 is a fast, security-hardened, GPS-referenced Stratum-1 Network Time Protocol (NTP) Server in a 1U half-rack sized, compact enclosure. It can provide a precise time reference for computer networks of almost any size and can accurately synchronize any NTP or SNTP compatible client.

With a powerful network optimized, 64-bit processor, the TA210 can process in excess of 20,000 NTP polls per second (1.2 million per minute) without affecting timing. Allowing a large number of network time clients to synchronise with extremely high precision.

Featuring Gigabit Ethernet (GbE) and a 72 channel GPS timing receiver which provides reliable reception of the GPS satellite system. TimeTools TA210 also incorporates a high-stability Temperature-Compensated Crystal Oscillator (TCXO), which provides extended Stratum-1 operation in the event of any loss of GNSS signal lock.



Designed and Manufactured In The UK.

Security-Hardened, GPS-Referenced Stratum-1 NTP v4 Network Time Server.

Fast, 20,000 NTP Polls Per Second (1.2M/minute), For Precise Client Synchronization.

High-Stability, Temperature-Compensated Crystal Oscillator (TCXO) For Extended Stratum-1 Operation In The Event Of Any Loss of GPS Signal Lock.

Network-Optimized Gigabit Ethernet (GbE).

NTP synchronization to <2 microseconds UTC (GPS Locked).

Advanced, 72 Channel, GPS Receiver For Reliable Reception Of The GPS Satellite System.

Powerful, Easy To Use, Web Interface With Command Line Interface For Advanced Users.

Full MD5, SHA1 and SHA256 NTP Authentication For Enhanced Security.

Peer To Multiple External NTP Servers For Improved Redundancy.

3-Year Warranty, Free Firmware Updates and Lifetime Support.

CE and UKCA Compliant With Full EMC and Electrical Safety Test Reports.



Applications

- Synchronize Microsoft Windows, Linux, servers, workstations and network infrastructure.
- Network timing, measurement and synchronization.
- Automation Systems, SCADA, Network Monitoring and Control Systems.
- CCTV, DVR and Video Management Systems (VMS).
- Access Control Systems (ACS).
- Master clock for NTP synchronized clock systems.
- Accurately synchronize time critical processes to a traceable source of time inside your firewall.

Key Features and Benefits

- Linux based true stratum-1 NTP time server.
- Extremely easy to install and configure.
- Powerful, easy to use, Web interface with Command Line Interface for advanced users.
- High-quality, 1U high, half-rack aluminium enclosure.
- USB Client port for convenient firmware updates.

NTP Timing Features

- Fast, 20,000 NTP Polls Per Second (1.2 Million Per Minute), for precise client synchronization.
- High-Stability, Temperature-Compensated Crystal Oscillator (TCXO) for extended Stratum-1 operation in the event of loss of GPS signal lock.
- NTP synchronization to <2 microseconds UTC (GPS Locked).
- Ability to synchronize in excess of 20 million clients at default NTP polling frequency.
- Peer to multiple external and internet based NTP servers.
- Full MD5, SHA1 and SHA256 Authentication for enhanced security.

Networking Features

- Network-optimized 10/100/1000 Mbit Auto-Sensing, Auto-MDIX Ethernet port.
- NTPv4, SNTPv4, HTTP, HTTPS, SSH, SCP, SFTP, FTP, SNMP v1/v2c/v3, DHCP, DHCPv6.
- IPv4 and IPv6 Internet Protocol.

GPS Timing Features

- Advanced, 72 channel, GPS timing receiver providing reception of GPS satellite signals.
- Timing receiver synchronizes to 30 nanoseconds RMS. (GPS locked).
- Fully automatic impending leap second warning and insertion, no user intervention required.
- High sensitivity GPS receiver.
- Advanced spoofing and jamming detection.
- Excellent RF interference mitigation.

Reliable and Environmentally Friendly

- Based on ultra-reliable industrial computing module.
- Very low-power consumption, less than 10W.
- CE and UKCA compliant with full EMC and Electrical Safety Test reports.
- RoHS compliant - Restriction on use of hazardous substances.

Warranty and Support

- 3-year warranty.
- Free firmware updates and unlimited email and telephone support for the lifetime of the product.



Copyright © 2025 TimeTools Limited.
All Rights Reserved.
All Trademarks Acknowledged.

TimeTools

Product Specification

System

64-Bit ARM Cortex-A72 Processor @ 800MHz.
8GB eMMC Flash Memory.
1GB SDRAM.

Interfaces

10/100/1000 Mbit Base-T, RJ45, Auto-Sensing Ethernet.
TNC RF Connector For Active GPS Antenna.
USB Client port for firmware updates.

Operating System

Flash-Based Linux Operating System.
Linux 6.2 LTS with PPS Extensions.

Internet Protocol (IP)

IPv4, IPv6.

Timing Protocols

NTP v2 (RFC 1119), NTP v3 (RFC 1305), NTP v4 (RFC 5905).
SNTP v3 (RFC 1769), SNTP v4 (RFC 2030).
NTP Peering, Unicast, Broadcast.
NTP MD5, SHA1, SHA256 Authentication.
Max. NTP Polling Freq.: 20,000 polls per second (1.2M/min).
Max. Clients at Default NTP Polling Freq.: 20,000,000

Configuration and Monitoring Protocols

HTTP, HTTPS, SSH, SCP, SFTP, FTP.
SNMP: v1, v2c, v3
Dynamic Host Configuration Protocol - DHCP (RFC 2131).
Dynamic Host Configuration Protocol - DHCPv6 (RFC 3315).

Timing (typical)

GPS Accuracy: RMS 30 nanoseconds (GPS Lock).
99% 60 nanoseconds (GPS Lock).
NTP Accuracy (GPS Lock): <2 microseconds.
Holdover (Typ): ± 0.5 ppm @ 25C (± 43 msec / 24 hours).
TCXO Crystal Ageing (First Year, 25°C, Typ.): ± 3 ppm.
TCXO Freq Stability vs. Temp (-40°C to +85°C): ± 5 ppm.

GPS Timing Receiver

72 Channel GPS receiver.
GPS L1 C/A Frequency Bands.
Advanced spoofing and jamming detection.
Excellent RF interference mitigation.
High Sensitivity Operation.

Update Rate: 1 Hz
Typical Tracking Sensitivity: -166dBm
Time to First Fix: <29s cold start
Typical Time to Re-acquisition: <2s

Mechanical \ Environmental

Dimensions (W x D x H): 220 x 120 x 44 mm
Construction: 1U High, Half-Rack, Aluminium
Weight: approx 1.2Kg

Power: 100-240VAC 50-60Hz 0.1A

Fuses: Two: T2A LBC 250V

Power Consumption: <10W

Double Fused IEC Inlet

Operating Temperature: -20°C ~ +60°C

Storage Temperature: -25°C ~ +70°C

Working Humidity: 80% RH non-condensing

MTBF (Processor Module): 143,000 hours
(PSU): 4,914,900 hours.

TW3040 GPS Antenna Specification

Freq. Band: 1575.42 MHz $\pm$ 10 MHz
Size: 66.5mm diameter x 21mm high.
Weight: 150g
Enclosure: Radome: LEXAN™ EXL9330, Base: Zamak Metal.
Attachment Method: Through hole (M18 x 1 thread)
Environmental: IP69K
Compliance: IPC-A-610, FCC, CE RED, RoHS, REACH
Operating Temperature: -40°C ~ +85°C

LNA Gain: 40 dB typical.

Supply Current: 15mA typical.

Supply Voltage: 2.5 to 16 VDC nominal

Approvals

CE: 2014/53/EU
2011/65/EU (EU RoHS 2)
2015/863 (EU RoHS 3).

UKCA: The Radio Equipment Regulations 2017
The RoHS Regulations 2013

Radio: EN 303 413 V1.2.1 (2021-4)
EN 301 489-1 V2.2.3 (2019-11)
EN 301 489-19 V2.1.1 (2019-4)

EMC: EN 55032: 2015
EN 55035:2017
EN 61000-3-2: 2014
EN 61000-3-3

Safety: EN 62368-1:2014+AC:2015

RoHS: EN IEC 63000:2018



Copyright © 2025 TimeTools Limited.
All Rights Reserved.
All Trademarks Acknowledged.

TimeTools

Ordering Information

Product Codes

TA210-P00 TimeTools TA210 GPS NTP Server Appliance
High-Gain GPS Timing Antenna.
GPS Antenna Mount.
20m Low-Loss Antenna Cable.
IEC Power Lead.
Quick Start Guide.
Manufactured in UK.
TA210-P00 Commodity Code: 84719000



TimeTools Limited has relied on representations made by its suppliers in certifying this product as RoHS compliant.

TimeTools Limited is not responsible for the availability, operation or failure of operation of GPS/GNSS satellites.

In no event will TimeTools Limited be liable for any indirect, special, incidental, or consequential damages from the sale or use of this product. This disclaimer applies both during and after the term of the warranty. TimeTools Limited disclaims liability for any implied warranties, including implied warranties of merchantability and fitness for a specific purpose.

All specifications subject to change without notice.

Terms and conditions of sale available on request.

Registered trademarks acknowledged. All rights reserved.

© 2025 TimeTools Limited. All Rights Reserved.

Options and Extras

CN-UB-280DC-SB Phoenix Contact GPS Surge Suppressor, essential for outdoor located Antennas.
Commodity Code: 85363010. Manufactured in Germany.

TCX-030S Pre-terminated 30m Low-Loss GPS Antenna Cable.
(Replaces 20m Low-Loss Antenna Cable).
Commodity Code: 8536691000. Manufactured in UK.

TCX-050S Pre-terminated 50m Low-Loss GPS Antenna Cable.
(Replaces 20m Low-Loss Antenna Cable).
Commodity Code: 8536691000. Manufactured in UK.

Customised Antenna Cables to accommodate specific installation requirements are available on request.

Contact Information

TimeTools Limited.
3 Silverend Business Park,
Brettell Lane,
Brierley Hill. DY5 3LG.
UK

Phone: +44 (0) 1384 623537
Email : Sales@TimeToolsLtd.com
Web: <https://TimeToolsLtd.com/>



Copyright © 2025 TimeTools Limited.
All Rights Reserved.
All Trademarks Acknowledged.

TimeTools